

Arandela para rodamiento axial de rodillos WS81114-SKF

WS81114-SKF

LE BON ROULEMENT

| Principal dimensions | | Basic load ratings | | Fatigue load limit | Minimum load factor | Speed ratings | Mass | Designation | | | | |
|----------------------|----|--------------------|----------------|--------------------|---------------------|----------------|----------------|-------------|-----------------|----------------|------|----------|
| d | D | H | E ₁ | E ₂ | C | C ₀ | P ₀ | A | Reference speed | Limiting speed | kg | |
| mm | | | | | ISO | ISO | | r/min | | | | |
| 70 | 95 | 18 | 12 | 12 | 66.5 | 145 | 14.5 | 0.0095 | 1700 | 3400 | 0.37 | 81114 TN |

| Dimensions | | Abutment and fillet dimensions | | | | Designation of components | | | Housing washer | Universal washer | | |
|------------|----------------|--------------------------------|------|----------------|------------------|---------------------------|----------------|----------------|---|------------------|----------|---------|
| d | d ₁ | D ₁ | B | E ₁ | r _{1,2} | r ₁ | r ₂ | r ₃ | Cylindrical roller bearing fit assembly | Short washer | | |
| mm | | | | | mm | mm | mm | mm | | | | |
| 70 | 55 | 72 | 6.25 | 7.5 | 0 | 12 | 12 | 1 | K 82114 TN | WS 81114 | GG-82114 | LS 7095 |



Arandela para rodamiento axial de rodillos WS81114-SKF

| Caractéristique | Valeur |
|----------------------------|---|
| d - Diámetro interior (mm) | 70 |
| D - Diámetro exterior (mm) | 95 |
| C - Espesor (mm) | 5,25 |
| Marca | SKF |
| Tipo del rodamiento | Arandela para rodamiento extrema presión y baja temperatura |
| Unidad de venta | pieza |

