

Rodamiento oscilante dos hileras de rodillos 22317-E-C4-SKF

22317-E-C4-SKF

LE BON ROULEMENT

Principal dimensions		Basic load ratings		Fatigue load limit	Speed ratings	Mass	Designations
d	D	B	C	C_0	Reference speed	Limiting speed	Bearing with cylindrical bore
mm			kN	kN	r/min	kg	
85	180	60	550	620	61	2800 3800 7,65	* 22317 E

Dimensions		Abutment and fillet dimensions			Calculation factors							
d	d_2	D_3	b	K	$r_{1,2}$	d_a min.	D_3 max.	r_a max.	α	Y_1	Y_2	Y_0
mm					mm							
85	108	154	8,3	4,5	3	99	166	2,5	0,33	2	3	2



Rodamiento oscilante dos hileras de rodillos 22317-E-C4-SKF

Caractéristique	Valeur
d - Diámetro interior (mm)	85
D - Diámetro exterior (mm)	180
C - Espesor (mm)	60
Marca	SKF
Tipo del rodamiento	Con rodillos oscilantes
Juego	Muy alta velocidad (C4)
Tipo de sellado	No estanco
Tipo de jaula	Acero
Agujero	Cilíndrico/a
Rodamiento serie	22300
Unidad de venta	pieza

