



Rodamiento oscilante dos hileras de rodillos 22320-E-JA-VA406-SKF

22320-E-JA-VA406-SKF



Principal dimensions			Basic load ratings		Fatigue load limit	Speed ratings		Mass	Designations	
d	D	B	C	C ₀	P ₀	Ref. speed	Lim. speed	kg	Bearing with cylindrical bore	tapered bore
mm			kN		kN	rpm				
100	215	75	815	950	88	2400	3000	13,5	* 22320-E-JA/VA406	=

Geometries					Abutment and fillet dimensions				Calculation factors			Permissible accelerations	
d	d ₂	D ₁	b	K	r _{1,2}	d _a	D _a	r _a	e	V ₁	V ₂	V ₃	
mm					mm	mm	mm	mm				m/s ²	
100	170	194	11,1	6	3	114	201	2,5	0,33	2	3	2	540 30g



**Rodamiento oscilante dos hileras de rodillos 22320-E-JA-
VA406-SKF**

Caractéristique	Valeur
d - Diámetro interior (mm)	100
D - Diámetro exterior (mm)	215
C - Espesor (mm)	73
Marca	SKF
Tipo del rodamiento	Con rodillos oscilantes
Juego	Estándar
Tipo de sellado	No estanco
Tipo de jaula	Acero
Agujero	Cilíndrico/a
Especificaciones	Para aplicacion vibrante
Rodamiento serie	22300
Unidad de venta	pieza

