

# Rodamiento oscilante dos hileras de rodillos 23138-CC-W33-C4-SKF

23138-CC-W33-C4-SKF

**LE BON ROULEMENT**

Principal dimensions		Basic load ratings		Fatigue load limit	Speed ratings	Mass	Designations			
d	D	B	C	$C_0$	Reference speed	Limiting speed	Bearing with cylindrical bore			
mm			kN	kN	r/min	kg				
190	320	304	1.370	2.080	183	1.500	2.000	35	* 23138 CC/W33	* 23138 CCK/W33

  

Dimensions					Abutment and fillet dimensions			Calculation factors				
d	$d_2$	$D_2$	b	K	$r_{2,2}$	$d_a$	$D_a$	$r_a$	$\epsilon$	$Y_1$	$Y_2$	$Y_0$
mm					mm	mm						
190	220	275	13,9	3,5	3	204	306	2,5	0,31	2,2	3,3	2,2



**Rodamiento oscilante dos hileras de rodillos 23138-CC-  
W33-C4-SKF**

<b>Caractéristique</b>	<b>Valeur</b>
d - Diámetro interior (mm)	190
D - Diámetro exterior (mm)	320
C - Espesor (mm)	104
Marca	SKF
Tipo del rodamiento	Con rodillos oscilantes
Juego	Muy alta velocidad (C4)
Tipo de sellado	No estanco
Tipo de jaula	Acero
Agujero	Cilíndrico/a
Rodamiento serie	23100
Unidad de venta	pieza

