



Rodamiento oscilante dos hileras de rodillos 24124-CC-W33-C4-SKF

24124-CC-W33-C4-SKF



Principal dimensions			Basic load ratings		Fatigue load limit	Speed ratings		Mass	Designations		
d	D	B	dynamic C	static C ₀	P ₀	Reference speed	Limiting speed	kg	Bearing with cylindrical bore	tapered bore	
mm			kN		kN	r/min					
120	200	80	655	950	95	1 900	2 600	30,5	* 24124 CC/W33	* 24124 CCK30/W33	

Dimensions						Abutment and fillet dimensions			Calculation factors			
d	d ₂	D ₁	b	K	r _{1,2}	d _a	D _a	r _a	v	Y ₁	Y ₂	Y ₀
mm					mm	mm	mm	mm				
120	135	148	6	3	2	131	189	2	0,37	1,8	2,7	5,8



Rodamiento oscilante dos hileras de rodillos 24124-CC- W33-C4-SKF

Caractéristique	Valeur
d - Diámetro interior (mm)	120
D - Diámetro exterior (mm)	200
C - Espesor (mm)	80
Marca	SKF
Tipo del rodamiento	Con rodillos oscilantes
Juego	Muy alta velocidad (C4)
Tipo de sellado	No estanco
Tipo de jaula	Acero
Agujero	Cilíndrico/a
Rodamiento serie	24100
Unidad de venta	pieza

