

# Rodamiento de rodillos cónicos 32020-X/Q-DF-SKF

## 32020-X/Q-DF-SKF

**LE BON ROULEMENT**

Principal dimensions			Basic load ratings		Fatigue load limit	Speed ratings		Mass	Designation
d	D	T	C	C <sub>0</sub>	F <sub>0</sub>	Reference speed	Limiting speed	kg	
mm			kN	kN	t/mk	rpm	rpm		
100	150	64	292	540	x2	2400	4000	3,96	32020 X/QDF

  

Dimensions				Abutment and fit dimensions						Calculation factors				
d	2B	r <sub>1,2</sub>	Y <sub>1,2</sub>	d <sub>1</sub>	D <sub>1</sub>	D <sub>2</sub>	C <sub>1</sub>	r <sub>1,2</sub>	s <sub>1</sub>	e	Y <sub>1</sub>	Y <sub>2</sub>	Y <sub>3</sub>	
mm		mm	mm	mm	mm	mm	mm	mm	mm					
100	64	1,6	0,4	110	134	142	4	1,6	0,6		0,36	0,6	2,2	1,4



**Rodamiento de rodillos cónicos 32020-X/Q-DF-SKF**

<b>Caractéristique</b>	<b>Valeur</b>
d - Diámetro interior (mm)	100
D - Diámetro exterior (mm)	150
C - Espesor (mm)	64
Marca	SKF
Tipo del rodamiento	Con rodillos cónicos
Rodamiento serie	32000
Unidad de venta	pieza

