

Rodamiento de rodillos cónicos T7FC060-Q-CL7C-SKF

T7FC060-Q-CL7C-SKF

LE BON ROULEMENT

Principal dimensions	Basic load ratings	Fatigue load limit	Speed ratings	Mass	Designation	Dimension series to ISO 285 (SMA)
d D T	C_0 C_1	P_0	Ref. speed Limit speed	kg		
mm	MM	MM	r/min			
60 125 27	154 204	34,5	3400 5300	2,05	T7FC060QCL7C	TFC

Dimensions			Mounting and fillet dimensions										Calculation factors					
d	d_1	B	C	$r_{1,2}$	$r_{3,4}$	a	e_1	e_2	D_1	D_2	D_3	C_1	C_2	T_1	T_2	α	Y	Y_2
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	°		
60	97,2	33,5	25	3	3	41	72	72	94	111	119	4	11	2,5	2,5	0,83	0,72	0,4



Rodamiento de rodillos cónicos T7FC060-Q-CL7C-SKF

Caractéristique	Valeur
d - Diámetro interior (mm)	60
D - Diámetro exterior (mm)	125
C - Espesor (mm)	37
Marca	SKF
Tipo del rodamiento	Con rodillos cónicos
Espesor de	33,5
Espesor de la cubeta	26
Rodamiento serie	ISO
Unidad de venta	pieza

