

Rodamiento de rodillos cónicos T7FC080-Q-CL7C-SKF

T7FC080-Q-CL7C-SKF

LE BON ROULEMENT

Principal dimensions	Basic load ratings	Fatigue load limit	Speed ratings	Mass	Designation	Dimension series to ISO 285 (SMA)
d D T	C_0 C_1	P_0	Ref. speed Limit speed	kg		
mm	kN	kN	r/min			
80 125 45	229 312	31.5	2600 4000	4	T7FC080QCL7C	TFC

Dimensions		Mounting and fillet dimensions										Calculation factors						
d	d_1	B	C	r_{12}	r_{14}	a	e_1	e_2	D_1	D_2	D_3	C_1	C_2	T_1	T_2	α	Y	Y_2
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	°		
80	125	41	31	3	3	53	94	92	122	148	122	5	14	2.5	2.5	0.68	0.68	0.4



Rodamiento de rodillos cónicos T7FC080-Q-CL7C-SKF

Caractéristique	Valeur
d - Diámetro interior (mm)	80
D - Diámetro exterior (mm)	160
C - Espesor (mm)	45
Marca	SKF
Tipo del rodamiento	Con rodillos cónicos
Espesor de	41
Espesor de la cubeta	31
Rodamiento serie	ISO
Unidad de venta	pieza

