



LE BON ROULEMENT



Principal dimensions			Basic lead ratings dynamic C_d		Fatigue lead rating static C_g		Speed ratings Refer- ence speed	Limit- ing speed	Mass	Designation	Dimension series to ISO 155 (ADDA)
d	D	T							kg	—	—
mm	mm	mm	N		N		mm/min	mm/min			
20	47	15.25	17.5	26	3	11010	11 060	0.13		3020A J2/Q	20B

Dimensions				Abutment and Fillet dimensions										Calculation factors				
d	d ₁	G	C	r _{2/2} (N1)	r _{2/2} (N2)	a	d ₄ (N1)	d ₄ (N2)	D ₄ (N1)	D ₄ (N2)	C ₁ (N1)	C ₁ (N2)	r ₄ (N1)	r ₄ (N2)	a	Y	Y ₂	
mm																		
20	33.7	14	12	1	1	11	27	26	40	41	43	2	3	1	1	0.35	3.7	0.6



Rodamiento de rodillos cónicos 7204-SKF

Caractéristique	Valeur
d - Diámetro interior (mm)	20
D - Diámetro exterior (mm)	47
C - Espesor (mm)	15,25
Marca	SKF
Tipo del rodamiento	Con rodillos cónicos
Espesor de	14
Espesor de la cubeta	12
Rodamiento serie	30200
Unidad de venta	pieza

