





LE BON ROULEMENT



| Principal Dimensions |          |          | Basic load ratings |                        | Fatigue load limit    |          | Speed ratings         |                       | Mass     |          | Designation |  | Dimension series for ISO 355 (ASMA) |  |
|----------------------|----------|----------|--------------------|------------------------|-----------------------|----------|-----------------------|-----------------------|----------|----------|-------------|--|-------------------------------------|--|
| <i>d</i>             | <i>D</i> | <i>T</i> | <i>C</i>           | <i>C</i> <sub>10</sub> | <i>P</i> <sub>0</sub> | <i>n</i> | <i>n</i> <sub>1</sub> | <i>n</i> <sub>2</sub> | <i>m</i> | <i>M</i> |             |  |                                     |  |
| mm                   | mm       | mm       | kN                 | kN                     | kN                    | 1/min    | 1/min                 | 1/min                 | kg       | kg       |             |  |                                     |  |
| 60                   | 230      | 32.5     | 148                | 194                    | 23.6                  | 4 000    | 5 300                 | 3 800                 | 1.8      | 1.8      | 30322 J2/Q  |  | 378                                 |  |

| Dimensions |                       |          |          | Abutment and Fillet dimensions |                                |          |                               |                               |                               |                               |                               |                               |                               | Calculation factors           |                               |          |          |                       |
|------------|-----------------------|----------|----------|--------------------------------|--------------------------------|----------|-------------------------------|-------------------------------|-------------------------------|-------------------------------|-------------------------------|-------------------------------|-------------------------------|-------------------------------|-------------------------------|----------|----------|-----------------------|
| <i>d</i>   | <i>d</i> <sub>1</sub> | <i>D</i> | <i>C</i> | <i>r</i> <sub>20</sub><br>(mm) | <i>r</i> <sub>25</sub><br>(mm) | <i>s</i> | <i>d</i> <sub>4</sub><br>(mm) | <i>d</i> <sub>5</sub><br>(mm) | <i>d</i> <sub>6</sub><br>(mm) | <i>D</i> <sub>4</sub><br>(mm) | <i>D</i> <sub>5</sub><br>(mm) | <i>C</i> <sub>4</sub><br>(mm) | <i>C</i> <sub>5</sub><br>(mm) | <i>T</i> <sub>4</sub><br>(mm) | <i>T</i> <sub>5</sub><br>(mm) | <i>s</i> | <i>Y</i> | <i>Y</i> <sub>s</sub> |
| mm         | mm                    | mm       | mm       | mm                             | mm                             | mm       | mm                            | mm                            | mm                            | mm                            | mm                            | mm                            | mm                            | mm                            | mm                            | mm       | mm       | mm                    |
| 60         | 91.8                  | 31       | 24       | 3                              | 2.5                            | 26       | 77                            | 72                            | 122                           | 118                           | 120                           | 5                             | 7.5                           | 3                             | 2.5                           | 0.35     | 1.7      | 0.6                   |



**Rodamiento de rodillos cónicos 7312-SKF**

| Caractéristique            | Valeur               |
|----------------------------|----------------------|
| d - Diámetro interior (mm) | 60                   |
| D - Diámetro exterior (mm) | 130                  |
| C - Espesor (mm)           | 33,5                 |
| Marca                      | SKF                  |
| Tipo del rodamiento        | Con rodillos cónicos |
| Espesor de                 | 31                   |
| Espesor de la cubeta       | 26                   |
| Rodamiento serie           | 30300                |
| Unidad de venta            | pieza                |

