



Rodamiento de rodillos cónicos 7317-SKF



Principal dimensions			Basic load ratings		Fatigue load		Speed ratings		Mass	Designation	Dimension series to ISO 3325 (ABMA)
<i>d</i>	<i>D</i>	<i>T</i>	<i>C</i> _{dyn}	<i>C</i> _{st}	<i>P</i> ₀	<i>P</i> ₁	Refr. speed	Limit speed			
mm	mm	mm	kN	kN	kN	kN	r/min	r/min	kg	—	—
55	280	44.5	303	365	40.5	2800	4000	4.82		30317 J2	368

Dimensions			Abutment and Fillet dimensions												Calculation factors			
<i>d</i>	<i>d</i> ₀	<i>G</i>	<i>C</i>	<i>r</i> _{1/2} (mm)	<i>r</i> _{2/3} (mm)	<i>a</i>	<i>d</i> ₁ (mm)	<i>d</i> ₂ (mm)	<i>D</i> ₁ (mm)	<i>D</i> ₂ (mm)	<i>C</i> ₁ (mm)	<i>C</i> ₂ (mm)	<i>r</i> _{1/2} (mm)	<i>r</i> _{2/3} (mm)	<i>a</i>	<i>Y</i>	<i>Y</i> ₀	
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm				
55	126	43	34	4	3	35	107	99	154	34.6	167	6	10.5	4	3	0.35	1.7	0.3



Rodamiento de rodillos cónicos 7317-SKF

Caractéristique	Valeur
d - Diámetro interior (mm)	85
D - Diámetro exterior (mm)	180
C - Espesor (mm)	44,5
Marca	SKF
Tipo del rodamiento	Con rodillos cónicos
Espesor de	41
Espesor de la cubeta	34
Rodamiento serie	30300
Unidad de venta	pieza

