



Rodamiento de rodillos cónicos 7112-SKF

32012-X/Q-CL7C-SKF


**LE BON
ROULEMENT**


Principal dimensions			Basic load ratings		Fatigue load limit	Speed ratings		Mass	Designation	Dimension series to ISO 285 (SMA)
d	D	T	C	C ₉₀	P ₀	Reference speed	Limiting speed	kg		
mm			kN		kN	r/min				
60	95	23	95	122	12.4	5 300	6 700	0.59	* 32012 X/QCL7C	40C

Dimensions			Abutment and fillet dimensions										Calculation factors		
d	d ₁	B	C	r _{3/2}	r _{4/2}	a	d ₄	d ₅	D ₄	D ₅	C ₄	C ₅	r ₆	r ₇	y ₂
mm				μm	μm		mm	mm	mm	mm	mm	mm	mm	mm	
60	77.8	23	17.5	1.5	1.5	21	67	67	85	88	91	4	5.5	1.5	1.5



Rodamiento de rodillos cónicos 7112-SKF

Caractéristique	Valeur
d - Diámetro interior (mm)	60
D - Diámetro exterior (mm)	95
C - Espesor (mm)	23
Marca	SKF
Tipo del rodamiento	Con rodillos cónicos
Espesor de	23
Espesor de la cubeta	17,5
Rodamiento serie	32000
Unidad de venta	pieza

