



Rodamiento de rodillos cónicos 7516-SKF

32216-J2/Q-SKF



Principal dimensions			Basic load ratings		Fatigue load limit	Speed ratings		Mass	Designation	Dimension series to ISO 285 (ASMA)
d	D	T	C	C_0	P_0	Reference speed	Limiting speed	kg		
mm			kN		kN	r/min				
80	540	35,25	187	240	38,5	3 400	4 500	3,08	32216 J2/Q	2DC

Dimensions				Abutment and fillet dimensions										Calculation factors		
d	d ₁	B	C	r_{D1}	r_{D2}	r_{D3}	r_{D4}	r_{D5}	r_{D6}	r_{D7}	r_{D8}	r_{D9}	r_{D10}	α	γ	γ_0
mm				μm	μm	μm	μm	μm	μm	μm	μm	μm	μm			
80	106	33	28	2,5	2	30	90	90	122	110	124	5	7	2,5	2	0,43 1,4 0,8



Rodamiento de rodillos cónicos 7516-SKF

Caractéristique	Valeur
d - Diámetro interior (mm)	80
D - Diámetro exterior (mm)	140
C - Espesor (mm)	35,25
Marca	SKF
Tipo del rodamiento	Con rodillos cónicos
Espesor de	33
Espesor de la cubeta	28
Rodamiento serie	32200
Unidad de venta	pieza

