



Rodamiento de rodillos cónicos 7517-SKF

32217-J2/Q-SKF



Principal dimensions	Basic load ratings dynamic C_1 static C_0	Fatigue load limit P_0	Speed ratings Reform- ance speed Limit- ing speed	Mass	Designation	Dimension series to ISO 355 (ABMA)
d D T						
mm	MM	kN	r/min	kg	—	—
BS 370 381.5	212 280	33.5	3 300 4 300	2.6	32247 J2/0	TEC

Dimensions				Abutment and fillet dimensions										Calculation factors			
d	d_0	D	C	$r_{D/2}$ mm	$r_{D/3}$ mm	a	d_1 mm	d_2 mm	D_1 mm	D_2 mm	C_1 mm	$r_{D/2}$ mm	$r_{D/3}$ mm	a	γ	γ_0	
mm							mm	mm	mm	mm	mm				—		
BS 113	36	80	2.5	2	33		96	95	130	140	142	5	8.5	2.5	2	0.43	0.4



Rodamiento de rodillos cónicos 7517-SKF

Caractéristique	Valeur
d - Diámetro interior (mm)	85
D - Diámetro exterior (mm)	150
C - Espesor (mm)	38,5
Marca	SKF
Tipo del rodamiento	Con rodillos cónicos
Espesor de	36
Espesor de la cubeta	30
Rodamiento serie	32200
Unidad de venta	pieza

