



32218-J2/Q-SKF



Principal dimensions			Basic load ratings		Fatigue load limit		Speed ratings		Mass	Designation	Dimension series to ISO 355 (ABMA)
<i>d</i>	<i>D</i>	<i>T</i>	<i>C</i> ₁₀	<i>C</i> ₀₁	<i>P</i> ₀	<i>P</i> ₁	Revolutions per minute	Limiting speed	<i>m</i>		
mm	mm	mm	kN	kN	kN	kN	r/min	m/min	kg	—	—
90	340	42.5	251	340	38	3 000	4 000	3.72	32218 Z/0		3FC

Dimensions			Abutment and fillet dimensions												Calculation factors			
<i>d</i>	<i>d</i> ₀	<i>G</i>	<i>C</i>	<i>r</i> ₁₂ (mm)	<i>r</i> ₁₄ (mm)	<i>a</i>	<i>d</i> ₁ (mm)	<i>d</i> ₂ (mm)	<i>D</i> ₁ (mm)	<i>D</i> ₂ (mm)	<i>C</i> ₁ (mm)	<i>C</i> ₂ (mm)	<i>r</i> ₁ (mm)	<i>r</i> ₂ (mm)	<i>k</i>	<i>Y</i>	<i>Y</i> ₀	
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm				
90	121	40	34	2.5	2	36	102	100	138	150	152	5	8.5	2.5	2	0.43	1.4	0.5



Rodamiento de rodillos cónicos 7518-SKF

Caractéristique	Valeur
d - Diámetro interior (mm)	90
D - Diámetro exterior (mm)	160
C - Espesor (mm)	42,5
Marca	SKF
Tipo del rodamiento	Con rodillos cónicos
Espesor de	40
Espesor de la cubeta	34
Rodamiento serie	32200
Unidad de venta	pieza

