



**LE BON
ROULEMENT**

Principal dimensions			Basic load ratings		Fatigue load limit	Speed ratings		Mass	Designation	Dimension series to ISO 355 (ABMA)
<i>d</i>	<i>D</i>	<i>T</i>	dynamic C_d	static C_s	P_0	Reference speed	Limiting speed			
mm	mm	mm	kN	kN	kN	r/min	r/min	kg	—	—
14.0	25.0	71.75	64.4	1.000	320	1.800	2.600	3.4	32228 J2	47D

Dimensions				Abutment and Fillet dimensions												Calculation factors		
<i>d</i>	d_0	<i>D</i>	<i>C</i>	$r_{D/2}$ mm	$r_{D/4}$ mm	<i>a</i>	d_1 mm	d_2 mm	d_3 mm	D_1 mm	D_2 mm	C_1 mm	C_2 mm	$r_{D/2}$ mm	$r_{D/4}$ mm	<i>a</i>	<i>f</i>	<i>g</i>
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
14.0	13.1	60	53	4	3	60	15.9	15.4	23.0	216	236	8	13.5	4	3	0.43	1.4	0.4



Rodamiento de rodillos cónicos 7528-SKF

Caractéristique	Valeur
d - Diámetro interior (mm)	140
D - Diámetro exterior (mm)	250
C - Espesor (mm)	71,75
Marca	SKF
Tipo del rodamiento	Con rodillos cónicos
Espesor de	68
Espesor de la cubeta	58
Rodamiento serie	32200
Unidad de venta	pieza

