



Rodamiento de rodillos cónicos 7617-SKF



Principal dimensions			Basic load ratings		Fatigue load limit	Speed ratings	Mass	Designation	Dimension series to ISO 3325 (ABMA)
<i>d</i>	<i>D</i>	<i>T</i>	<i>C</i> ₁₀	<i>C</i> ₉₀	<i>P</i> ₀	Reference speed	Limiting speed		
mm	mm	mm	kN	kN	kN	r/min	r/min	kg	—
55	580	675	400	530	80	2 800	4 000	7.1	32337 J2
									360

Dimensions				Abutment and Fillet dimensions												Calculation factors		
<i>d</i>	<i>d</i> ₁	<i>G</i>	<i>C</i>	<i>r</i> ₂₃ (mm)	<i>r</i> ₂₄ (mm)	<i>a</i>	<i>r</i> ₁₀ (mm)	<i>r</i> ₁₁ (mm)	<i>r</i> ₁₂ (mm)	<i>D</i> ₁ (mm)	<i>D</i> ₂ (mm)	<i>C</i> ₁ (mm)	<i>C</i> ₂ (mm)	<i>r</i> ₁₃ (mm)	<i>r</i> ₁₄ (mm)	<i>a</i>	<i>Y</i>	<i>Y</i> ₂
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm			
55	127	60	49	4	3	42	100	99	150	348	167	8	34.5	4	3	0.35	1.7	0.9



Rodamiento de rodillos cónicos 7617-SKF

Caractéristique	Valeur
d - Diámetro interior (mm)	85
D - Diámetro exterior (mm)	180
C - Espesor (mm)	63,5
Marca	SKF
Tipo del rodamiento	Con rodillos cónicos
Espesor de	60
Espesor de la cubeta	49
Rodamiento serie	32300
Unidad de venta	pieza

