



Rodamiento de rodillos cónicos 7619-SKF



Principal dimensions			Basic load ratings		Fatigue load limit		Speed ratings		Mass	Designation	Dimension series to ISO 355 (ABMA)
<i>d</i>	<i>D</i>	<i>T</i>	<i>C</i> ₁₀	<i>C</i> ₀	<i>P</i> ₀	Revolutions per minute	Limiting speed	<i>m</i>			
mm	mm	mm	kN	kN	kN	r/min	m/s	kg	—	—	
95	200	71.8	501	670	72	2400	3400	9.8	32319 J2	360	

Dimensions				Abutment and fillet dimensions												Calculation factors		
<i>d</i>	<i>d</i> ₀	<i>g</i>	<i>C</i>	<i>r</i> _{1/2} (mm)	<i>r</i> _{1/2} (in)	<i>a</i>	<i>d</i> ₁ (mm)	<i>d</i> ₂ (mm)	<i>D</i> ₁ (mm)	<i>D</i> ₂ (mm)	<i>C</i> ₁ (mm)	<i>C</i> ₂ (mm)	<i>r</i> _{1/4} (mm)	<i>r</i> _{1/4} (in)	<i>k</i>	<i>Y</i>	<i>Y</i> ₀	
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm				
95	143	67	55	4	3	47	115	109	166	186	8	16.5	4	3	0.35	1.7	0.9	



Rodamiento de rodillos cónicos 7619-SKF

Caractéristique	Valeur
d - Diámetro interior (mm)	95
D - Diámetro exterior (mm)	200
C - Espesor (mm)	71,5
Marca	SKF
Tipo del rodamiento	Con rodillos cónicos
Espesor de	67
Espesor de la cubeta	55
Rodamiento serie	32300
Unidad de venta	pieza

