



Rodamiento de rodillos cilíndricos NUP210-ET-C3-NSK

NUP210-ET-C3-NSK


**LE BON
ROULEMENT**


Dimensions (mm)							Capacité de Charge (N)		Vitesses Limites (m/min)	
d	D	B	r	r1	Fe	En	C1	C0	Grisse	Halle
50	50	20	1.1	1.1	59.5	—	69 000	70 500	6 300	7 500

Référence Roulement					Dimensions Cotes de Montage (mm)										Mass (kg)
NU	NJ	NUP	N	HF	d ₁	d ₂	d ₃	d ₄	D ₁	D ₂	D ₃	D ₄	r ₁	r ₂	approx
					min	min	max	min	max	max	min	max	max	max	
NU 210 ET	NU	NJ	NUP	—	56.5	56.5	57	62	67	63.5	—	—	1	1	0.50



Rodamiento de rodillos cilíndricos NUP210-ET-C3-NSK

Caractéristique	Valeur
d - Diámetro interior (mm)	50
D - Diámetro exterior (mm)	90
C - Espesor (mm)	20
Marca	NSK
Tipo del rodamiento	Con rodillos cilíndricos
Juego	Alta velocidad (C3, J30)
Tipo de jaula	Poliamido
Rodamiento serie	NUP200
Unidad de venta	pieza

