


Rodamiento de rodillos cilíndricos NUP212-E-M6-NKE

NUP212-E-M6-NKE

 **LE BON
ROULEMENT**



NUP...

Hauptabmessungen [mm]			Tragzahlen [kN]			Stetiglaufzahlen [min ⁻¹]		Grenzlaufzahlen [min ⁻¹]		Lagertyp	Alternative Käfige
Boundary dimensions [mm]			Load ratings [kN]			Thermal speed ratings [rpm]		Limit speed ratings [rpm]		Designation	Alternative cages
d	D	B	C _r dyn	C ₀ stat	C ₉₀	n _{th}	n ₀				
60	110	22	106	105	12,7	5400	7500			NUP212-E-TVP3	M5, M46, MPA

Lagerabmessungen [mm]								Winkelring		Gewicht [kg]	
Bearing dimensions [mm]								Thrust collar		Weight [kg]	
d	E, F	d ₁	D ₁	r ₁ , r ₂ min	r ₃ , r ₄ min	s	Bezeichnung Designation	B ₁	B ₂	Lager Bearing	Winkelring Thrust collar
60	72	77,7	96,7	1,5	1,5	—	—	—	—	1	—



Rodamiento de rodillos cilíndricos NUP212-E-M6-NKE

Caractéristique	Valeur
d - Diámetro interior (mm)	60
D - Diámetro exterior (mm)	110
C - Espesor (mm)	22
Marca	NKE
Tipo del rodamiento	Con rodillos cilíndricos
Juego	Estándar
Tipo de jaula	Macisa latón
Rodamiento serie	NUP200
Unidad de venta	pieza

