



Rodamiento de rodillos cilíndricos NUP2205-ET-C3-NSK

NUP2205-ET-C3-NSK



Dimensions (mm)							Capacité de Charge (N)		Vitesses Limitées (tr/min)	
d	D	B	r	r1	Fw	En	C _r	C ₀	Gralité	Haut
25	52	18	1	0.6	31.5	—	35 000	34 500	12 000	54 000

Référence Roulement					Dimensions Cotes de Montage (mm)										Mass kg	
	NU	NJ	NUP	N	NF	d ₁ mm	d ₂ mm	d ₃ mm	d ₄ mm	d ₅ mm	D ₁ mm	D ₂ mm	r _s mm	r _e mm	approx.	
NU2205 ET	NU	NJ	NUP	—	—	30	29	30	34	37	47	—	—	1	0.6	0.10



Rodamiento de rodillos cilíndricos NUP2205-ET-C3-NSK

Caractéristique	Valeur
d - Diámetro interior (mm)	25
D - Diámetro exterior (mm)	52
C - Espesor (mm)	18
Marca	NSK
Tipo del rodamiento	Con rodillos cilíndricos
Juego	Alta velocidad (C3, J30)
Tipo de jaula	Poliamido
Rodamiento serie	NUP2200
Unidad de venta	pieza

