

Rodamiento de rodillos cilíndricos NUP2215-E-TVP3-NKE

NUP2215-E-TVP3-NKE

**LE BON
ROULEMENT**

NUP...

Hauptabmessungen [mm] Boundary dimensions [mm]			Tragzahlen [kN] Load ratings [kN]			Referenzdrehzahlen [min ⁻¹] Thermal speed ratings [rpm]		Grenzdrehzahlen [min ⁻¹] Limit speed ratings [rpm]		Lagertypen Designation	Alternative Käfige Alternative cages
d	D	B	C ₉₀ dyn	C ₁₀ stat	C ₁₀	n _{th}	n ₂				
75	130	31	162	210	29.3	3700	6000	NUP2215-E-TVP3		M6, MA6, MPA	

Lagerabmessungen [mm] Bearing dimensions [mm]								Winkelring Thrust collar		Gewicht [kg] Weight [kg]	
d	E, F	d ₁	D ₁	r ₁ , r ₂ min	r ₃ , r ₄ min	s	Bezeichnung Designation	B ₁	B ₂	Lager Bearing	Winkelring Thrust collar
75	88.5	94.5	113.5	1.5	1.5	--	--	--	--	1.8	--



Rodamiento de rodillos cilíndricos NUP2215-E-TVP3-NKE

Caractéristique	Valeur
d - Diámetro interior (mm)	75
D - Diámetro exterior (mm)	130
C - Espesor (mm)	31
Marca	NKE
Tipo del rodamiento	Con rodillos cilíndricos
Juego	Estándar
Tipo de jaula	Poliamido
Rodamiento serie	NUP2200
Unidad de venta	pieza

