

Rodamiento de rodillos cilíndricos NUP2310-E-M6-NKE

NUP2310-E-M6-NKE

**LE BON
ROULEMENT**

NUP...

Hauptabmessungen [mm] Boundary dimensions [mm]			Tragzahlen [kN] Load ratings [kN]			Rollenstetigkeit [min ⁻¹] Thermal speed ratings [rpm]		Grenzstetigkeit [min ⁻¹] Limited speed ratings [rpm]		Lagertyp Designation	Alternative Käfige Alternative cages
d	D	B	C _d dyn	C ₀ stat	C ₁₀	n _{th}	n ₀				
90	110	40	162	189	23	5000	8000			NUP2310-E-TVP3	NR, MA6, MPA

Lagerabmessungen [mm] Bearing dimensions [mm]							Winkelring Thrust collar			Gewicht [kg] Weight [kg]	
d	E,F	d ₁	D ₁	r ₁ , r ₂ min	r ₃ , r ₄ min	s	Bezeichnung Designation	B ₁	B ₂	Lager Bearing	Winkelring Thrust collar
90	66	71.2	92	2	2	--	--	--	--	1.9	--



Rodamiento de rodillos cilíndricos NUP2310-E-M6-NKE

Caractéristique	Valeur
d - Diámetro interior (mm)	50
D - Diámetro exterior (mm)	110
C - Espesor (mm)	40
Marca	NKE
Tipo del rodamiento	Con rodillos cilíndricos
Juego	Estándar
Tipo de jaula	Macisa latón
Rodamiento serie	NUP2300
Unidad de venta	pieza

