

Rodamiento de rodillos cilíndricos NUP2312-E-TVP3-NKE

NUP2312-E-TVP3-NKE

**LE BON
ROULEMENT**

NUP...

Hauptabmessungen [mm]			Tragzahlen [kN]			Stetendrehzahl [min ⁻¹]		Grenzrehzahl [min ⁻¹]		Lagertyp	Alternative Käfige
Boundary dimensions [mm]			Load ratings [kN]			Thermal speed ratings [rpm]		Limit speed ratings [rpm]		Designation	Alternative cages
d	D	B	C _r dyn	C ₀ stat	C ₉₀	n _{th}	n ₀				
60	130	46	250	265	32,3	4300	6700			NUP2312-E-TVP3	M5, M46, MPA

Lagerabmessungen [mm]						Winkelring			Gewicht [kg]		
Bearing dimensions [mm]						Thrust collar			Weight [kg]		
d	E.F	d ₁ =	D ₁ =	r ₁ , r ₂ min	r ₃ , r ₄ min	s	Bezeichnung Designation	B ₁	B ₂	Lager Bearing	Winkelring Thrust collar
60	77	84,5	110	2,1	2,1	—	—	—	—	2,9	—



Rodamiento de rodillos cilíndricos NUP2312-E-TVP3-NKE

Caractéristique	Valeur
d - Diámetro interior (mm)	60
D - Diámetro exterior (mm)	130
C - Espesor (mm)	46
Marca	NKE
Tipo del rodamiento	Con rodillos cilíndricos
Juego	Estándar
Tipo de jaula	Poliamido
Rodamiento serie	NUP2300
Unidad de venta	pieza

