

Rodamiento de rodillos cilíndricos NUP2313-E-MPA-NKE

NUP2313-E-MPA-NKE

**LE BON
ROULEMENT**

NUP...

Hauptabmessungen [mm] Boundary dimensions [mm]			Tragzahlen [kN] Load ratings [kN]			Befestigungszahlen [min] Thrust speed ratings [rpm]		Grenzrehzahlen [min] Limit speed ratings [rpm]		Lagertypen Designation	Alternative Käfige Alternative cages
d	D	B	C _{dyn}	C _{stat}	C ₁₀	n _{th}	n _{so}				
65	140	48	277	289	34,9	4100	6000	NUP2313-E-TVP3		M6, M46, MPA	

Lagerabmessungen [mm] Bearing dimensions [mm]								Winkelring Thrust collar		Gewicht [kg] Weight [kg]	
d	E, F	d ₁	D ₁	r ₁ , r ₂ min	r ₃ , r ₄ min	s	Bezeichnung Designation	B ₁	B ₂	Lager Bearing	Winkelring Thrust collar
65	82,5	90,7	118,5	2,1	2,1	—	—	—	—	3,3	—



Rodamiento de rodillos cilíndricos NUP2313-E-MPA-NKE

Caractéristique	Valeur
d - Diámetro interior (mm)	65
D - Diámetro exterior (mm)	140
C - Espesor (mm)	48
Marca	NKE
Tipo del rodamiento	Con rodillos cilíndricos
Juego	Estándar
Tipo de jaula	Macisa latón
Rodamiento serie	NUP2300
Unidad de venta	pieza

