

Rodamiento de rodillos cilíndricos NUP2318-E-TVP3-NKE

NUP2318-E-TVP3-NKE

**LE BON
ROULEMENT**

NUP...

Hauptabmessungen [mm]	Tragzahlen [kN]	Rollerendzählzahlen [min ⁻¹]	Grenzrehzahlen [min ⁻¹]	Lagertypen [mm]	Alternative Käfige
Boundary dimensions [mm]	Load ratings [kN]	Thermal speed ratings [rpm]	Limited speed ratings [rpm]	Designation	Alternative cages
d D B	C _{dyn} C _{stat}	n _b	n ₂		
90 190 64	486 536 59	3000	4500	NUP2318-E-TVP3	M6, M46, MFA

Lagerabmessungen [mm]							Winkelring Thrust collar		Gewicht [kg]		
Bearing dimensions [mm]											
d	E,F	d ₁	D ₁	r ₁ , r ₂ min	r ₃ , r ₄ min	s	Bezeichnung Designation	B ₁	B ₂	Lager Bearing	Winkelring Thrust collar
		=	=			=					
90	113.5	124	161.4	3	3	—	—	—	—	8.1	—



Rodamiento de rodillos cilíndricos NUP2318-E-TVP3-NKE

Caractéristique	Valeur
d - Diámetro interior (mm)	90
D - Diámetro exterior (mm)	190
C - Espesor (mm)	64
Marca	NKE
Tipo del rodamiento	Con rodillos cilíndricos
Juego	Estándar
Tipo de jaula	Poliamido
Rodamiento serie	NUP2300
Unidad de venta	pieza

