

Rodamiento de rodillos cilíndricos NUP308-E-TVP3-NKE

NUP308-E-TVP3-NKE

**LE BON
ROULEMENT**

NUP...

Hauptabmessungen [mm] Boundary dimensions [mm]			Tragzahlen [kN] Load ratings [kN]			Referenzdrehzahlen [min ⁻¹] Thrust speed refsg [rpm]		Grenzdrehzahlen [min ⁻¹] Limit speed refsg [rpm]		Lagertyp Designation	Alternative Käfige Alternative cages
d	D	B	C _{dyn}	C _{stat}	C ₁₀	n _{ref}	n _{lim}	n ₂			
40	90	23	91	80	9.7	7200	2500			NUP308-E-TVP3	MPA

Lagerabmessungen [mm] Bearing dimensions [mm]						Winkelring Thrust collar				Gewicht [kg] Weight [kg]	
d	E,F	d ₁	D ₁	r ₁ , r ₂ min	r ₃ , r ₄ min	s	Bezeichnung Designation	B ₂	B ₃	Lager Bearing	Winkelring Thrust collar
40	52	57.7	74.9	1.5	1.5	—	—	—	—	0.95	—



Rodamiento de rodillos cilíndricos NUP308-E-TVP3-NKE

Caractéristique	Valeur
d - Diámetro interior (mm)	40
D - Diámetro exterior (mm)	90
C - Espesor (mm)	23
Marca	NKE
Tipo del rodamiento	Con rodillos cilíndricos
Juego	Estándar
Tipo de jaula	Poliamido
Rodamiento serie	NUP300
Unidad de venta	pieza

