


Rodamiento de rodillos cilíndricos NUP314-E-M6-NKE

NUP314-E-M6-NKE

 **LE BON
ROULEMENT**



NUP...

Hauptabmessungen [mm]			Tragzahlen [kN]			Befestigungszahl [min ⁻¹]		Grenzgeschwindigkeiten [min ⁻¹]		Lagertyp	Alternative Käfige
Boundary dimensions [mm]			Load ratings [kN]			Thrust speed ratings [rpm]		Limit speed ratings [rpm]		Designation	Alternative cages
d	D	B	C _{dyn}	C _{stat}	C ₁₀	n _{thr}	n _{lim}				
70	150	35	229	224	25.5	4500	5600			NUP314-E-TVP3	MB, MAB, MPA

Lagerabmessungen [mm]								Winkelring		Gewicht [kg]	
Bearing dimensions [mm]								Thrust collar		Weight [kg]	
d	E, F	d ₁	D ₁	r ₁ , r ₂	r ₃ , r ₄	*	Bezeichnung Designation	B ₁	B ₂	Lager Bearing	Winkelring Thrust collar
70	85	97.5	126.4	2.1	2.1	—	—	—	—	2.8	—



Rodamiento de rodillos cilíndricos NUP314-E-M6-NKE

Caractéristique	Valeur
d - Diámetro interior (mm)	70
D - Diámetro exterior (mm)	150
C - Espesor (mm)	35
Marca	NKE
Tipo del rodamiento	Con rodillos cilíndricos
Juego	Estándar
Tipo de jaula	Macisa latón
Rodamiento serie	NUP300
Unidad de venta	pieza

