

Rodamiento de rodillos cilíndricos NUP316-E-M6-NKE

NUP316-E-M6-NKE

**LE BON
ROULEMENT**

NUP...

Hauptabmessungen [mm] Boundary dimensions [mm]			Tragzahlen [kN] Load ratings [kN]			Referenzdrehzahlen [min ⁻¹] Thermal speed ratings [rpm]		Grenzdrehzahlen [min ⁻¹] Limit speed ratings [rpm]		Lagertypen Designation	Alternative Käfige Alternative cages
d	D	B	C ₉₀ dyn	C ₉₀ stat	C ₉₀	n _{th}	n ₂				
80	170	38	290	285	32.9	4100	5000			NUP316-E-TVP3	M6, M46, MPA

Lagerabmessungen [mm] Bearing dimensions [mm]							Winkelring Thrust collar			Gewicht [kg] Weight [kg]	
d	E, F	d ₁	D ₁	r ₁ , r ₂ min	r ₃ , r ₄ min	s	Bezeichnung Designation	B ₁	B ₂	Lager Bearing	Winkelring Thrust collar
80	101	—	143.7	2.1	2.1	0.7	—	—	—	3.95	—



Rodamiento de rodillos cilíndricos NUP316-E-M6-NKE

Caractéristique	Valeur
d - Diámetro interior (mm)	80
D - Diámetro exterior (mm)	170
C - Espesor (mm)	39
Marca	NKE
Tipo del rodamiento	Con rodillos cilíndricos
Juego	Estándar
Tipo de jaula	Macisa latón
Rodamiento serie	NUP300
Unidad de venta	pieza

