


# Rodamiento de rodillos cilíndricos NUP411-M-NKE

## NUP411-M-NKE

 **LE BON  
ROULEMENT**



NUP...

| Hauptabmessungen<br>[mm]<br>Boundary dimensions<br>[mm] |     |    | Tragzahlen<br>[kN]<br>Load ratings<br>[kN] |                        |                 | Stetigdrehzahl<br>[min <sup>-1</sup> ]<br>Thermal speed<br>ratings [rpm] |                | Grenzrehzahl<br>[min <sup>-1</sup> ]<br>Limit speed<br>ratings [rpm] |  | Lagertyp<br>Designation | Alternative<br>Käfige<br>Alternative<br>cages |
|---------------------------------------------------------|-----|----|--------------------------------------------|------------------------|-----------------|--------------------------------------------------------------------------|----------------|----------------------------------------------------------------------|--|-------------------------|-----------------------------------------------|
| d                                                       | D   | B  | C <sub>r</sub><br>dyn                      | C <sub>0</sub><br>stat | C <sub>90</sub> | n <sub>th</sub>                                                          | n <sub>0</sub> |                                                                      |  |                         |                                               |
| 55                                                      | 140 | 33 | 142                                        | 142                    | 17.3            | 5400                                                                     | 5300           |                                                                      |  | NUP411-M                | —                                             |

| Lagerabmessungen<br>[mm]<br>Bearing dimensions<br>[mm] |      |                |                |                                        |                                        |   |                            | Winkelring<br>Thrust collar |                | Gewicht<br>[kg]<br>Weight<br>[kg] |                             |
|--------------------------------------------------------|------|----------------|----------------|----------------------------------------|----------------------------------------|---|----------------------------|-----------------------------|----------------|-----------------------------------|-----------------------------|
| d                                                      | E.F  | d <sub>1</sub> | D <sub>1</sub> | r <sub>1</sub> , r <sub>2</sub><br>min | r <sub>3</sub> , r <sub>4</sub><br>min | s | Bezeichnung<br>Designation | B <sub>1</sub>              | B <sub>2</sub> | Lager<br>Bearing                  | Winkelring<br>Thrust collar |
| 55                                                     | 77.2 | 85.2           | 110            | 2.1                                    | 2.1                                    | — | —                          | —                           | —              | 2.5                               | —                           |



**Rodamiento de rodillos cilíndricos NUP411-M-NKE**

| Caractéristique            | Valeur                   |
|----------------------------|--------------------------|
| d - Diámetro interior (mm) | 55                       |
| D - Diámetro exterior (mm) | 140                      |
| C - Espesor (mm)           | 33                       |
| Marca                      | NKE                      |
| Tipo del rodamiento        | Con rodillos cilíndricos |
| Juego                      | Estándar                 |
| Tipo de jaula              | Macisa latón             |
| Rodamiento serie           | NUP400                   |
| Unidad de venta            | pieza                    |

