

Rodamiento de rodillos cilíndricos NN3021-K-TN9-SP-W33-SKF

NN3021-K-TN9-SP-W33-SKF

LE BON ROULEMENT

| Principal dimensions | | Basic load ratings | | Fatigue load limit | | Attainable speeds | | Mass | Designations | |
|----------------------|-----|--------------------|-----|--------------------|----------------|-------------------|--------------------|-----------------|-----------------------------|------------------|
| d | D | B | C | C ₀ | P ₀ | Cr | Grease lubrication | Oil lubrication | Seating with a tapered bore | Cylindrical bore |
| mm | mm | mm | kN | kN | kN | min | min | kg | | |
| 305 | 350 | 41 | 100 | 305 | 36 | 5 300 | 6 000 | 2,7 | NN 3021 KTN/SP | NN 3021 TN/SP |

| Dimensions | | | | Abutment and fillet dimensions | | | | | | | | Reference gross quantity | | | |
|------------|----------------|------|----|--------------------------------|------------------|------------------|----------------|----------------|----------------|----------------|----------------|--------------------------|----------------|----------------|-------------------|
| d | d ₁ | E, F | b | K | r _{1,2} | r _{3,4} | r ₅ | r ₆ | r ₇ | r ₈ | D ₁ | D ₂ | r ₉ | d ₉ | C _{ref} |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | (x ³) |
| 305 | 125,2 | 144 | - | - | 2 | 1,5 | 2 | 115 | - | - | 148 | 190 | 2 | 144,1 | 12 |



Rodamiento de rodillos cilíndricos NN3021-K-TN9-SP-W33-SKF

| Caractéristique | Valeur |
|----------------------------|--------------------------|
| d - Diámetro interior (mm) | 105 |
| D - Diámetro exterior (mm) | 160 |
| C - Espesor (mm) | 41 |
| Marca | SKF |
| Tipo del rodamiento | Con rodillos cilíndricos |
| Juego | Estándar |
| Tipo de sellado | No estanco |
| Tipo de jaula | Poliamido |
| Agujero | Cónico/a |
| Rodamiento serie | NN3000 |
| Unidad de venta | pieza |

