

Rodamiento de rodillos cilíndricos NNU4926-B-K-SP-W33-SKF

NNU4926-B-K-SP-W33-SKF

LE BON ROULEMENT

Principal dimensions	Basic load ratings	Fatigue load limit	Attainable speeds	Mass	Designations
d D B	C C ₀	P ₀	Grease lubrication Oil-air lubrication	kg	Bearing with a tapered bore cylindrical bore
130 382 50	187 390	41.5	4 300 4 800	3.05	NNU4926 BK/SPW33 NNU4926 B/SPW33

Dimensions	Abutment and fillet dimensions										Reference grease quantity							
d	d ₁	D ₁	E	F	b	K	r _{3,2}	r _{4,2}	r	r _{4,1}	r _{3,1}	r ₄	r ₃	D ₁	D ₂	r ₁	d ₁	
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	cm ³
130	162	246	5.5	3	1.5	1	2.2	137	144	149	—	172	1.5	167	31			



Rodamiento de rodillos cilíndricos NNU4926-B-K-SP-W33-SKF

Caractéristique	Valeur
d - Diámetro interior (mm)	130
D - Diámetro exterior (mm)	180
C - Espesor (mm)	50
Marca	SKF
Tipo del rodamiento	Con rodillos cilíndricos
Juego	Estándar
Tipo de sellado	No estanco
Tipo de jaula	Acero
Agujero	Cónico/a
Rodamiento serie	NNU4900
Unidad de venta	pieza

