


Rodamiento de rodillos cilíndricos NU1012-M-NKE

NU1012-M-NKE

 **LE BON
ROULEMENT**



NU...

Hauptabmessungen [mm] Boundary dimensions [mm]			Tragzahlen [kN] Load ratings [kN]			Stetigdrehzahl [min ⁻¹] Thermal speed ratings [rpm]		Grenzrehzahl [min ⁻¹] Limit speed ratings [rpm]		Lagertyp Designation	Alternative Käfige Alternative cages
d	D	B	C _d dyn	C ₀ stat	C ₉₀	n _{th}	n ₀				
60	95	18	95	68	8,3	6200	11000			NU1012-E-MPA	M6

Lagerabmessungen [mm] Bearing dimensions [mm]							Winkelring Thrust collar			Gewicht [kg] Weight [kg]	
d	E, F	d ₁ =	D ₁ =	r ₁ , r ₂ min	r ₃ , r ₄ min	s	Bezeichnung Designation	B ₁	B ₂	Lager Bearing	Winkelring Thrust collar
60	68	—	83	1,1	1	1,5	—	—	—	0,48	—



Rodamiento de rodillos cilíndricos NU1012-M-NKE

Caractéristique	Valeur
d - Diámetro interior (mm)	60
D - Diámetro exterior (mm)	95
C - Espesor (mm)	18
Marca	NKE
Tipo del rodamiento	Con rodillos cilíndricos
Juego	Estándar
Tipo de jaula	Macisa latón
Rodamiento serie	NU1000
Unidad de venta	pieza

