

Rodamiento de rodillos cilíndricos NU1016-M-C3-NKE

NU1016-M-C3-NKE

**LE BON
ROULEMENT**

NU...

Hauptabmessungen [mm] Boundary dimensions [mm]			Tragzahlen [kN] Load ratings [kN]			Referenzdrehzahlen [min ⁻¹] Thermal speed ratings [rpm]		Grenzdrehzahlen [min ⁻¹] Limit speed ratings [rpm]		Lagertypen Designation	Alternative Käfige Alternative cages
d	D	B	C ₉₀ dyn	C ₁₀₀ stat	C ₁₀	n _{ref}		n ₂			
80	125	22	101	132	16	4800		6300		NU1016-E-MPA	M6

Lagerabmessungen [mm] Bearing dimensions [mm]							Winkelring Thrust collar			Gewicht [kg] Weight [kg]	
d	E, F	d ₁ =	D ₂ =	r ₁ , r ₂ min	r ₃ , r ₄ min	s =	Bezeichnung Designation	B ₂	B ₃	Lager Bearing	Winkelring Thrust collar
80	91	—	110	1,1	1	1,7	—	—	—	1,03	—



Rodamiento de rodillos cilíndricos NU1016-M-C3-NKE

Caractéristique	Valeur
d - Diámetro interior (mm)	80
D - Diámetro exterior (mm)	125
C - Espesor (mm)	22
Marca	NKE
Tipo del rodamiento	Con rodillos cilíndricos
Juego	Alta velocidad (C3, J30)
Tipo de jaula	Macisa latón
Rodamiento serie	NU1000
Unidad de venta	pieza

