


Rodamiento de rodillos cilíndricos NU203-E-TVP3-C3-NKE

NU203-E-TVP3-C3-NKE

 **LE BON
ROULEMENT**



NU...

Hauptabmessungen [mm] Boundary dimensions [mm]			Tragzahlen [kN] Load ratings [kN]			Reinheitswerte [min] Thermal speed ratings [rpm]		Greiswerte [min] Limit speed ratings [rpm]		Lagertyp Designation	Alternative Käfige Alternative cages
d	D	B	C ₉₀ dyn.	C ₁₀ stat.	C ₁₂	n _{th}	n _g				
17	40	12	17.7	14.7	1.8	15400	22000			NU203-E-TVP3	—

Lagerabmessungen [mm] Bearing dimensions [mm]							Winkelring Thrust collar			Gewicht [kg] Weight [kg]	
d	E, F	d ₁	D ₁	r ₁ , r ₂ min	r ₃ , r ₄ min	s	Bezeichnung Designation	B ₁	B ₂	Lager Bearing	Winkelring Thrust collar
17	22.1	—	32	0.6	0.3	1.2	—	—	—	0.068	—



Rodamiento de rodillos cilíndricos NU203-E-TVP3-C3-NKE

Caractéristique	Valeur
d - Diámetro interior (mm)	17
D - Diámetro exterior (mm)	40
C - Espesor (mm)	12
Marca	NKE
Tipo del rodamiento	Con rodillos cilíndricos
Juego	Alta velocidad (C3, J30)
Tipo de jaula	Poliamido
Rodamiento serie	NU200
Unidad de venta	pieza

