



Rodamiento de rodillos cilíndricos NU206-ET-NSK

NU206-ET-NSK


**LE BON
ROULEMENT**


Dimensions (mm)							Capacité de Charge (N)		Vitesses Limitées (tr/min)	
d	D	B	r	r1	Fw	En	C _r	C ₀	Outside	Idle
20	62	16	1	0.6	375	—	39 500	37 500	6 500	12 000

Référence Roulement					Dimensions Cotes de Montage (mm)												Maxim (µm)
NU	NJ	NUP	N	NF	d ₁ min	d ₂ min	d ₃ max	d ₄ min	d ₅ max	D ₁ max	D ₂ max	D ₃ min	P ₁ max	P ₂ max	approx		
NU 206 ET	NU	NJ	NUP	—	26	34	26	40	44	57	—	—	1	0.6	0.205		



Rodamiento de rodillos cilíndricos NU206-ET-NSK

Caractéristique	Valeur
d - Diámetro interior (mm)	30
D - Diámetro exterior (mm)	62
C - Espesor (mm)	16
Marca	NSK
Tipo del rodamiento	Con rodillos cilíndricos
Juego	Estándar
Tipo de jaula	Poliamido
Rodamiento serie	NU200
Unidad de venta	pieza

