

Rodamiento de rodillos cilíndricos NU208-E-TVP3-C3-NKE

NU208-E-TVP3-C3-NKE

**LE BON
ROULEMENT**

NU...

Hauptabmessungen [mm] Boundary dimensions [mm]			Tragzahlen [kN] Load ratings [kN]			Referenzdrehzahlen [min ⁻¹] Thermal speed ratings [rpm]	Grenzdrehzahlen [min ⁻¹] Limited speed ratings [rpm]	Lagertypen Designation	Alternative Käfige Alternative cages
d	D	B	C _d	C _r	C ₉₀	n _{th}	n _c		

40	80	18	61	55	6,7	7600	11000	NU208-E-TVP3	MPA
----	----	----	----	----	-----	------	-------	--------------	-----

Lagerabmessungen [mm] Bearing dimensions [mm]							Winkelring Thrust collar			Gewicht [kg] Weight [kg]	
d	E, F	d ₁	D ₁	r ₁ , r ₂	r ₃ , r ₄	s	Bezeichnung Designation	B ₁	B ₂	Lager Bearing	Winkelring Thrust collar
		≅	≅	min	min						

40	49,5	—	67,3	1,1	1,1	1,9	—	—	—	0,36	—
----	------	---	------	-----	-----	-----	---	---	---	------	---



Rodamiento de rodillos cilíndricos NU208-E-TVP3-C3-NKE

Caractéristique	Valeur
d - Diámetro interior (mm)	40
D - Diámetro exterior (mm)	80
C - Espesor (mm)	18
Marca	NKE
Tipo del rodamiento	Con rodillos cilíndricos
Juego	Alta velocidad (C3, J30)
Tipo de jaula	Poliamido
Rodamiento serie	NU200
Unidad de venta	pieza

