

Rodamiento de rodillos cilíndricos NU213-E-M6-NKE

NU213-E-M6-NKE

**LE BON
ROULEMENT**

NU...

Hauptabmessungen [mm] Boundary dimensions [mm]			Tragzahlen [kN] Load ratings [kN]			Sukursdrehzahlen [min ⁻¹] Thermal speed ratings [rpm]		Greszdrehzahlen [min ⁻¹] Limited speed ratings [rpm]		Lagertype Designation	Alternative Käfige Alternative cages
d	D	B	C _{dyn}	C _{stat}	C ₁₀	n _{th}	n _l				
65	120	23	121	121	14,8	5000	6700			NU213-E-TVP3	M6, M46, MPA

Lagerabmessungen [mm] Bearing dimensions [mm]							Winkelring Thrust collar			Gewicht [kg] Weight [kg]	
d	E, F	d ₁	D ₁	r ₁ , r ₂ min	r ₃ , r ₄ min	s	Bezeichnung Designation	B ₁	B ₂	Lager Bearing	Winkelring Thrust collar
65	78,5	—	104	1,5	1,5	1,4	—	—	—	1,05	—



Rodamiento de rodillos cilíndricos NU213-E-M6-NKE

Caractéristique	Valeur
d - Diámetro interior (mm)	65
D - Diámetro exterior (mm)	120
C - Espesor (mm)	23
Marca	NKE
Tipo del rodamiento	Con rodillos cilíndricos
Juego	Estándar
Tipo de jaula	Macisa latón
Rodamiento serie	NU200
Unidad de venta	pieza

