

Rodamiento de rodillos cilíndricos NU215-E-M6-NKE

NU215-E-M6-NKE

**LE BON
ROULEMENT**

NU...

Hauptabmessungen [mm]			Tragzahlen [kN]			Befestigungszahlen [min ⁻¹]		Grenzrehzahlen [min ⁻¹]		Lagertyp	Alternative Käfige
Boundary dimensions [mm]			Load ratings [kN]			Thrust speed ratings [rpm]		Limit speed ratings [rpm]		Designation	Alternative cages
d	D	B	C _r dyn	C _{0r} stat	C ₉₀	n _{th}	n ₀	n ₀₁	n ₀₂		
75	130	25	147	159	19.2	4500	5000			NU215-E-TVP3	MS, MA6, MPA

Lagerabmessungen [mm]							Winkelring			Gewicht [kg]	
Bearing dimensions [mm]							Thrust collar			Weight [kg]	
d	E, F	d ₁	D ₁	r ₁ , r ₂ min	r ₃ , r ₄ min	*	Bezeichnung Designation	B ₁	B ₂	Lager Bearing	Winkelring Thrust collar
75	88.5	—	113.5	1.5	1.5	1.2	—	—	—	1.25	—



Rodamiento de rodillos cilíndricos NU215-E-M6-NKE

Caractéristique	Valeur
d - Diámetro interior (mm)	75
D - Diámetro exterior (mm)	130
C - Espesor (mm)	25
Marca	NKE
Tipo del rodamiento	Con rodillos cilíndricos
Juego	Estándar
Tipo de jaula	Macisa latón
Rodamiento serie	NU200
Unidad de venta	pieza

