

Rodamiento de rodillos cilíndricos NU215-E-TVP3-NKE

NU215-E-TVP3-NKE

**LE BON
ROULEMENT**

NU...

Hauptabmessungen [mm] Boundary dimensions [mm]			Tragzahlen [kN] Load ratings [kN]			Befestigungszahlen [min] Thrust speed [rpm]		Grenzgeschwindigkeiten [min] Limit speed [rpm]		Lagertypen Designation	Alternative Käfige Alternative cages
d	D	B	C _r dyn.	C ₀ stat.	C ₁₀	n _{thr}	n _{lim}				
75	130	25	147	159	19.2	4500	5000	NU215-E-TVP3			MS, MA5, MPA

Lagerabmessungen [mm] Bearing dimensions [mm]							Winkelring Thrust collar			Gewicht [kg] Weight [kg]	
d	E, F	d ₁	D ₁	r ₁ , r ₂ min	r ₃ , r ₄ min	*	Bezeichnung Designation	B ₁	B ₂	Lager Bearing	Winkelring Thrust collar
75	88.5	—	113.5	1.5	1.5	1.2	—	—	—	1.25	—



Rodamiento de rodillos cilíndricos NU215-E-TVP3-NKE

Caractéristique	Valeur
d - Diámetro interior (mm)	75
D - Diámetro exterior (mm)	130
C - Espesor (mm)	25
Marca	NKE
Tipo del rodamiento	Con rodillos cilíndricos
Juego	Estándar
Tipo de jaula	Poliamido
Rodamiento serie	NU200
Unidad de venta	pieza

