

Rodamiento de rodillos cilíndricos NU216-E-M6-NKE

NU216-E-M6-NKE

**LE BON
ROULEMENT**

NU...

Hauptabmessungen [mm] Boundary dimensions [mm]			Tragzahlen [kN] Load ratings [kN]			Referenzdrehzahlen [min ⁻¹] Thermal speed ratings [rpm]		Grenzdrehzahlen [min ⁻¹] Limit speed ratings [rpm]		Lagertypen Designation	Alternative Käfige Alternative cages
d	D	B	C ₉₀ dyn	C ₁₀ stat	C ₁₀	n _{th}	n ₂				
80	140	26	157	170	20,1	4200	5600			NU216-E-TVP3	M6, MA6, MPA

Lagerabmessungen [mm] Bearing dimensions [mm]							Winkelring Thrust collar			Gewicht [kg] Weight [kg]	
d	E, F	d ₁	D ₂	r ₁ , r ₂ min	r ₃ , r ₄ min	s	Bezeichnung Designation	B ₂	B ₃	Lager Bearing	Winkelring Thrust collar
80	95,3	—	122,3	2	2	1,3	—	—	—	1,54	—



Rodamiento de rodillos cilíndricos NU216-E-M6-NKE

Caractéristique	Valeur
d - Diámetro interior (mm)	80
D - Diámetro exterior (mm)	140
C - Espesor (mm)	26
Marca	NKE
Tipo del rodamiento	Con rodillos cilíndricos
Juego	Estándar
Tipo de jaula	Macisa latón
Rodamiento serie	NU200
Unidad de venta	pieza

