

Rodamiento de rodillos cilíndricos NU216-E-TVP3-NKE

NU216-E-TVP3-NKE

**LE BON
ROULEMENT**

NU...

Hauptabmessungen [mm] Boundary dimensions [mm]			Tragzahlen [kN] Load ratings [kN]			Referenzdrehzahlen [min ⁻¹] Thermal speed ratings [rpm]		Grenzdrehzahlen [min ⁻¹] Limit speed ratings [rpm]		Lagertypen Designation	Alternative Käfige Alternative cages
d	D	B	C ₁₀ dyn	C ₉₀ stat	C ₅₀	n _{ref}	n _{lim}	n ₂			
80	140	26	157	170	20,1	4200	5600			NU216-E-TVP3	M6, MA6, MPA

Lagerabmessungen [mm] Bearing dimensions [mm]							Winkelring Thrust collar			Gewicht [kg] Weight [kg]	
d	E, F	d ₁ =	D ₂ =	r ₁ , r ₂ min	r ₃ , r ₄ min	s =	Bezeichnung Designation	B ₁	B ₂	Lager Bearing	Winkelring Thrust collar
80	95,3	—	122,3	2	2	1,3	—	—	—	1,54	—



Rodamiento de rodillos cilíndricos NU216-E-TVP3-NKE

Caractéristique	Valeur
d - Diámetro interior (mm)	80
D - Diámetro exterior (mm)	140
C - Espesor (mm)	26
Marca	NKE
Tipo del rodamiento	Con rodillos cilíndricos
Juego	Estándar
Tipo de jaula	Poliamido
Rodamiento serie	NU200
Unidad de venta	pieza

