


Rodamiento de rodillos cilíndricos NU2215-E-TVP3-NKE

NU2215-E-TVP3-NKE

 **LE BON
ROULEMENT**



NU...

Hauptabmessungen [mm]			Tragzahlen [kN]			Befestigungszahlen [min ⁻¹]		Grenzrehzahlen [min ⁻¹]		Lagertyp	Alternative Käfige
Boundary dimensions [mm]			Load ratings [kN]			Thrust speed ratings [rpm]		Limit speed ratings [rpm]		Designation	Alternative cages
d	D	B	C _{dyn}	C _{stat}	C ₉₀	n _{thr}	n _{lim}				
75	130	31	162	210	25.3	3700	6000			NU2215-E-TVP3	MB, MAB, MPA

Lagerabmessungen [mm]							Winkelring			Gewicht [kg]	
Bearing dimensions [mm]							Thrust collar			Weight [kg]	
d	E, F	d _i	D _i	r ₁ , r ₂	r ₃ , r ₄	*	Bezeichnung Designation	B ₁	B ₂	Lager Bearing	Winkelring Thrust collar
75	88.5	—	113.5	1.5	1.5	1.6	—	—	—	1.6	—



Rodamiento de rodillos cilíndricos NU2215-E-TVP3-NKE

Caractéristique	Valeur
d - Diámetro interior (mm)	75
D - Diámetro exterior (mm)	130
C - Espesor (mm)	31
Marca	NKE
Tipo del rodamiento	Con rodillos cilíndricos
Juego	Estándar
Tipo de jaula	Poliamido
Rodamiento serie	NU2200
Unidad de venta	pieza

