

Rodamiento de rodillos cilíndricos NU2310-E-M6-NKE

NU2310-E-M6-NKE

**LE BON
ROULEMENT**

NU...

Hauptabmessungen [mm] Boundary dimensions [mm]			Tragzahlen [kN] Load ratings [kN]			Rollendrehzahlen [min ⁻¹] Thrust speed ratings [rpm]		Geszdrehzahlen [min ⁻¹] Limited speed ratings [rpm]		Lagertypen Designation	Alternative Käfige Alternative cages
d	D	B	C ₁₀ dyn.	C ₉₀ stat.	C ₅₀	n ₁₀	n ₅₀	n ₉₀			
50	110	40	162	189	23	5000	8000			NU2310-E-TVP3	MS, MAS, MPA

Lagerabmessungen [mm] Bearing dimensions [mm]							Winkelring Thrust collar			Gewicht [kg] Weight [kg]	
d	E, F	d ₁	D ₂	r ₁ , r ₂ min	r ₃ , r ₄ min	s	Bezeichnung Designation	B ₁	B ₂	Lager Bearing	Winkelring Thrust collar
50	66	—	92	2	2	3.2	—	—	—	1.9	—



Rodamiento de rodillos cilíndricos NU2310-E-M6-NKE

Caractéristique	Valeur
d - Diámetro interior (mm)	50
D - Diámetro exterior (mm)	110
C - Espesor (mm)	40
Marca	NKE
Tipo del rodamiento	Con rodillos cilíndricos
Juego	Estándar
Tipo de jaula	Macisa latón
Rodamiento serie	NU2300
Unidad de venta	pieza

