


Rodamiento de rodillos cilíndricos NU303-E-TVP3-C3-NKE

NU303-E-TVP3-C3-NKE

 **LE BON
ROULEMENT**



NU...

Hauptabmessungen [mm] Boundary dimensions [mm]			Tragzahlen [kN] Load ratings [kN]			Reinheitswerte [min ⁻¹] Thermal speed ratings [rpm]		Greiswerte [min ⁻¹] Limit speed ratings [rpm]		Lagertyp Designation	Alternative Käfige Alternative cages
d	D	B	C _{dyn}	C _{stat}	C ₁₀	n _{th}	n _{gr}				
17	47	14	25.5	21.3	2.6	13600	20000			NU303-E-TVP3	—

Lagerabmessungen [mm] Bearing dimensions [mm]						Winkelring Thrust collar				Gewicht [kg] Weight [kg]	
d	E, F	d ₁	D ₁	r ₁ , r ₂ min	r ₃ , r ₄ min	s	Bezeichnung Designation	B ₁	B ₂	Lager Bearing	Winkelring Thrust collar
17	24.2	—	38.8	1.1	0.6	1.1	—	—	—	0.12	—



Rodamiento de rodillos cilíndricos NU303-E-TVP3-C3-NKE

Caractéristique	Valeur
d - Diámetro interior (mm)	17
D - Diámetro exterior (mm)	47
C - Espesor (mm)	14
Marca	NKE
Tipo del rodamiento	Con rodillos cilíndricos
Juego	Alta velocidad (C3, J30)
Tipo de jaula	Poliamido
Rodamiento serie	NU300
Unidad de venta	pieza

