


Rodamiento de rodillos cilíndricos NU304-E-TVP3-NKE

NU304-E-TVP3-NKE

 **LE BON
ROULEMENT**



NU...

Hauptabmessungen [mm] Boundary dimensions [mm]			Tragzahlen [kN] Load ratings [kN]			Reinradrehzahl [min ⁻¹] Thermal speed ratings [rpm]		Grenzrehzahlen [min ⁻¹] Limit speed ratings [rpm]		Lagertyp Designation	Alternative Käfige Alternative cages
d	D	B	C _{dyn}	C _{stat}	C ₁₀	n _{th}	n _{lc}				
20	52	15	34,7	25,5	3,2	12200	18000			NU304-E-TVP3	—

Lagerabmessungen [mm] Bearing dimensions [mm]							Winkelring Thrust collar			Gewicht [kg] Weight [kg]	
d	E, F	d ₁	D ₁	r ₁ , r ₂ min	r ₃ , r ₄ min	s	Bezeichnung Designation	B ₁	B ₂	Lager Bearing	Winkelring Thrust collar
20	27,5	—	42	1,1	0,6	1,1	—	—	—	0,151	—



Rodamiento de rodillos cilíndricos NU304-E-TVP3-NKE

Caractéristique	Valeur
d - Diámetro interior (mm)	20
D - Diámetro exterior (mm)	52
C - Espesor (mm)	15
Marca	NKE
Tipo del rodamiento	Con rodillos cilíndricos
Juego	Estándar
Tipo de jaula	Poliamido
Rodamiento serie	NU300
Unidad de venta	pieza

