


Rodamiento de rodillos cilíndricos NU319-E-M6-NKE

NU319-E-M6-NKE

 **LE BON
ROULEMENT**



NU...

Hauptabmessungen [mm] Boundary dimensions [mm]			Tragzahlen [kN] Load ratings [kN]			Reinradrehzahl [min ⁻¹] Thermal speed ratings [rpm]		Greisradrehzahl [min ⁻¹] Limit speed ratings [rpm]		Lagertyp Designation	Alternative Käfige Alternative cages
d	D	B	C ₁₀ dyn.	C ₀ stat.	C ₉₀	n _{th}	n _g				
95	200	45	374	389	42	3600	4300			NU319-E-M6	—

Lagerabmessungen [mm] Bearing dimensions [mm]							Winkelring Thrust collar			Gewicht [kg] Weight [kg]	
d	E, F	d ₁	D ₁	r ₁ , r ₂ min	r ₃ , r ₄ min	s	Bezeichnung Designation	B ₁	B ₂	Lager Bearing	Winkelring Thrust collar
95	177,5	132,2	—	3	3	1,4	—	—	—	8,3	—



Rodamiento de rodillos cilíndricos NU319-E-M6-NKE

Caractéristique	Valeur
d - Diámetro interior (mm)	95
D - Diámetro exterior (mm)	200
C - Espesor (mm)	45
Marca	NKE
Tipo del rodamiento	Con rodillos cilíndricos
Juego	Estándar
Tipo de jaula	Macisa latón
Rodamiento serie	NU300
Unidad de venta	pieza

