


Rodamiento de rodillos cilíndricos NU320-E-TVP3-NKE

NU320-E-TVP3-NKE

 **LE BON
ROULEMENT**



NU...

Hauptabmessungen [mm] Boundary dimensions [mm]			Tragzahlen [kN] Load ratings [kN]			Reinradrehzahl [min ⁻¹] Thermal speed ratings [rpm]		Greisradrehzahl [min ⁻¹] Limit speed ratings [rpm]		Lagertyp Designation	Alternative Käfige Alternative cages
d	D	B	C _{dyn}	C _{stat}	C ₁₀	n _{th}	n _g				
100	215	47	430	435	46.1	3400	3800			NU320-E-TVP3	ML, MA6, MPA

Lagerabmessungen [mm] Bearing dimensions [mm]							Winkelring Thrust collar			Gewicht [kg] Weight [kg]	
d	E, F	d ₁	D ₁	r ₁ , r ₂ min	r ₃ , r ₄ min	s	Bezeichnung Designation	B ₁	B ₂	Lager Bearing	Winkelring Thrust collar
100	127.5	-	182.5	3	3	1.2	-	-	-	7.7	-



Rodamiento de rodillos cilíndricos NU320-E-TVP3-NKE

Caractéristique	Valeur
d - Diámetro interior (mm)	100
D - Diámetro exterior (mm)	215
C - Espesor (mm)	47
Marca	NKE
Tipo del rodamiento	Con rodillos cilíndricos
Juego	Estándar
Tipo de jaula	Poliamido
Rodamiento serie	NU300
Unidad de venta	pieza

