

Rodamiento de bolas a rótula 1305-EKTN9-C3

1305-EKTN9-C3

LE BON ROULEMENT

| Dimensions (mm) Dimension (mm) | | | Coefficient de charge (kN) Load rating (kN) | | Vitesse limite (tr/min) Speed limit (Rpm) | | Poids (kg) Weight (kg) | Style Designation | |
|-----------------------------------|-----------|-----------|--|----------------------------|--|-------|---------------------------|---|---------------------------------|
| d (mm) | D (mm) | B (mm) | Dynamique C _d | Statique C _s | Lubrification Lubrication | | | Alésage cylindrique Cylindrical bore | Alésage conique Tapered bore |
| 28 | 62 | 17 | 16.61 | 5.26 | 11075 | 11000 | 0.26 | 1305 | 1305K |



Rodamiento de bolas a rótula 1305-EKTN9-C3

| Caractéristique | Valeur |
|----------------------------|--------------------------|
| d - Diámetro interior (mm) | 25 |
| D - Diámetro exterior (mm) | 62 |
| C - Espesor (mm) | 17 |
| Marca | Genérica alta calidad |
| Tipo del rodamiento | De bolas |
| Juego | Alta velocidad (C3, J30) |
| Tipo de sellado | No estanco |
| Tipo de jaula | Poliamido |
| Agujero | Cónico/a |
| Rodamiento serie | 1300 |
| Unidad de venta | pieza |

