

# Rodamiento de bolas a rótula 1224-M-C3-SKF

1224-M-C3-SKF

**LE BON ROULEMENT**

Principal dimensions		Basic load ratings		Fatigue load limit	Speed ratings		Mass	Designations			
d	D	B	C	C <sub>10</sub>	F <sub>0</sub>	Reference speed	Limiting speed	kg	Bearing with cylindrical bore		tapered bore
mm			mm	mm	kN	min	min		1224M		1224KM
129	215	42	127	63	2,12	≤ 300	≤ 1000	6,75	1224M		1224KM

  

Dimensions				Abutment and fillet dimensions			Calculation factors					
d	d <sub>2</sub>	D <sub>1</sub>	r <sub>1,2</sub> min.	r <sub>1</sub> min.	D <sub>2</sub> max.	r <sub>2</sub> max.	i	e	f <sub>1</sub>	f <sub>2</sub>	Y <sub>1</sub>	Y <sub>2</sub>
mm				mm								
129	145	190	2,1	132	203	2		0,04	0,29	3,3	5,1	3,6



**Rodamiento de bolas a rótula 1224-M-C3-SKF**

<b>Caractéristique</b>	<b>Valeur</b>
d - Diámetro interior (mm)	120
D - Diámetro exterior (mm)	215
C - Espesor (mm)	42
Marca	SKF
Tipo del rodamiento	De bolas
Juego	Alta velocidad (C3, J30)
Tipo de sellado	No estanco
Tipo de jaula	Macisa latón
Agujero	Cilíndrico/a
Rodamiento serie	1200
Unidad de venta	pieza

